



**40 mm x 65 mm x 22 mm SKF NKIS 40  
cylindrical roller bearings**

Bearing No. NKIS 40

NKIS 40 Bearing 2D drawings and 3D CAD models

Size	65x40x22 mm
Bore Diameter	65 mm
Outer Diameter	40 mm
Width	22 mm
d	40 mm
D	65 mm
B	22 mm
F	50 mm
r <sub>1,2</sub> - min.	1 mm
s	0.5 mm
d <sub>a</sub> - min.	45 mm
D <sub>a</sub> - max.	60 mm
r <sub>a</sub> - max.	1 mm
Basic dynamic load rating - C	42.9 kN
Basic static load rating - C <sub>0</sub>	72 kN
Fatigue load limit - P <sub>u</sub>	8.8 kN
Reference speed	8000 r/min
Limiting speed	9000 r/min
Category	Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.295
EAN	7316577712066



## NTN BEARING MANUFACTURING DE MEXICO,S...

Product Group	B04144
bore diameter:	40 mm
dynamic load capacity:	42.9 kN
outside diameter:	65 mm
static load capacity:	72 kN
overall width:	22 mm
maximum rpm:	9000 rpm
needle bearing type:	Machined Bearing with Inner Ring
flanges:	With Flanges
closure type:	Open
series:	NKIS
number of rows:	One
lubrication hole type:	Hole on Outer Ring
bearing material:	Steel
precision rating:	Not Rated
operating temperature range:	Maximum of +250 ° F ° F
manufacturer upc number:	7316577712066
cage material:	Steel
r <sub>1,2</sub> min.	1 mm
s max.	0.5 mm
d <sub>a</sub> min.	45 mm
D <sub>a</sub> max.	60 mm
r <sub>a</sub> max.	1 mm
Basic dynamic load rating C	42.9 kN
Basic static load rating C <sub>0</sub>	72 kN
Fatigue load limit P <sub>u</sub>	8.8 kN
Mass bearing	0.28 kg