



177,8 mm x 247,65 mm x 47,625 mm Timken
67791/67720 tapered roller bearings

Bearing No. 67791/67720

67791/67720 Bearing 2D drawings and 3D CAD models

| | |
|---------------------------------|------------------------|
| Size | 177.8x247.65x47.625 mm |
| Bore Diameter | 177,8 mm |
| Outer Diameter | 247,65 mm |
| Width | 47,625 mm |
| d | 177,8 mm |
| D | 247,65 mm |
| T | 47,625 mm |
| B | 47,625 mm |
| C | 38,1 mm |
| R | 10,4 mm |
| r | 3,3 mm |
| a | 4,8 mm |
| Da | 240 mm |
| db | 208 mm |
| da | 188 mm |
| Db | 229 mm |
| Aa | 4,8 mm |
| Ab | 1,8 mm |
| Weight | 6,42 Kg |
| Basic static load rating (C0) | 779 kN |
| Factor (G1) | 622,3 |
| Factor (G2) | 122,6 |
| Factor (Cg) | 0,0339 |
| Factor (K) | 1,33 |
| Basic dynamic load rating (C90) | 97,2 |



NTN BEARING MANUFACTURING DE MEXICO,S...

| | |
|-------------------------------------|--------|
| Basic dynamic load rating (Ca90) | 73,2 |
| Basic dynamic load rating (C1) | 375 kN |
| Calculation factor (e) | 0,44 |